



## **TRUCK STOCK CLASS DEMOLITION DERBY RULES 2009**

1. Refer to General Rules for non-building rules.
2. Rules are the same as Stock Rules for cars with the following modifications:
  - a. Open to 1/2 ton 2X4 trucks or 1/2 ton suburbans only. No four wheel drives or 3/4 ton trucks. No ambulances or military vehicles. If in doubt, please call.
  - b. No body or suspension lift kits allowed. Maximum bumper height of 28" to the bottom of the bumper.
  - c. Only 5-lug or 6-lug rear-ends are allowed. May be welded or spooled.
  - d. Gas tank mounted in cab or in front of box. Must be secured, safe and covered.
  - e. Front bumper and rear bumper must remain stock. The bumpers may be trimmed, but not replaced. No ag-type, automotive or C-channel bumpers allowed.
  - f. Dash, seat and door bars are highly recommended. They should be welded or bolted securely to keep the driver protected. No size restriction on bars. Use heavy material such as channel iron or tube steel. Bars may be bolted or welded to the frame and/or the body and cannot extend more than 24" past rear of cab and must not extend further forward than the firewall.
  - g. Box may be bolted to frame in (8) places with 1" max diameter bolts. Washers or plates may be no larger than 6" x 6" x 1/4". Washers and plates may not be welded to the frame or the box.
  - h. Tailgate can be bolted or chained shut in (6) places, with bolts no bigger than 1" in diameter. Tailgates can also be welded shut with two 4" x 4" x 1/4" plates, one per side.

For questions please contact:

Steve Heitman at 612.741.5941 or [sheitman@impdemoderby.com](mailto:sheitman@impdemoderby.com)